

Product Information Sheet

Ideal LithoSeal

Over Print Varnish

DESCRIPTION

Ideal LithoSeal offers a premium range of sheetfed offset, oil-based overprint varnishes designed for high-performance finishes and protection. Whether you're seeking a brilliant shine or a subtle matte effect, our range has you covered.

Ideal LithoSeal Non-Yellowing High Gloss OPV

Achieve a vibrant, reflective finish that enhances color depth and vibrancy. This product features fast-drying properties and excellent rub and scuff resistance. Gloss Range: 70 - 80 GU on a 60° angle on a gloss meter. High Rub and Wax Free versions are available.

Ideal LithoSeal Non-Yellowing Satin OPV

A smooth, refined sheen that balances gloss with a touch of softness. This product features fast-drying properties and excellent rub and scuff resistance. Gloss Range: 30 - 40 GU on a 60° angle on a gloss meter.

Ideal LithoSeal Non-Yellowing Ultra Dull OPV

Perfect for creating a non-reflective, muted matte finish that exudes sophistication. This product features fast-drying properties and excellent rub and scuff resistance. Gloss Range: 10 GU on a 60° angle on a gloss meter.

Ideal LithoSeal Smooth Strike-Thu OPV

Designed for precise strike-through effects, giving you a tactile and visual contrast.

Ideal LithoSeal High Gloss OPV

Achieve a vibrant, reflective finish that enhances color depth and vibrancy. This product features fast-drying properties and excellent rub and scuff resistance. Gloss Range: 70 - 80 GU on a 60° angle on a gloss meter. High Rub and Wax Free versions are available.

Ideal LithoSeal Satin OPV

A smooth, refined sheen that balances gloss with a touch of softness. This product features fast-drying properties and excellent rub and scuff resistance. Gloss Range: 30 - 40 GU on a 60° angle on a gloss meter. Wax Free version available.

Ideal LithoSeal Ultra Dull OPV

Phone: 905-696-9818

Perfect for creating a non-reflective, muted matte finish that exudes sophistication. This product features fast-drying properties and excellent rub and scuff resistance. Gloss Range: 10 GU on a 60° angle on a gloss meter.



COMPATIBLE ADDITIVES

Driers:

Ideal Multi Drier Ideal Hard Dry Compound

PACKAGING

2.50 KG Slip Cover cans 10.00 KG Plastic Pails



PLEASE REFER TO SAFETY DATA SHEETS BEFORE USE

Molnar Lithographic Supplies (1986) Inc.

Email: orderdesk@idealgraphicsupplies.com